



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number : **0 516 417 A1**

(12)

EUROPEAN PATENT APPLICATION

(21) Application number : 92304845.8

(22) Date of filing : 28.05.92

(51) Int. Cl.⁵ : **H01M 8/12, H01M 8/24,
C25B 1/04**

(30) Priority : 30.05.91 JP 127883/91
30.01.92 JP 14808/92
12.07.91 JP 172012/91

(43) Date of publication of application :
02.12.92 Bulletin 92/49

(84) Designated Contracting States :
CH DE FR GB LI

(71) Applicant : MITSUBISHI JUKOGYO
KABUSHIKI KAISHA
5-1, Marunouchi 2-chome Chiyoda-ku
Tokyo (JP)

(72) Inventor : Uchida, Satoshi, c/o Nagasaki
Shipyards & Eng. Works
Mitsubishi Jukogyo K.K., 1-1, Akunoura-machi
Nagasaki, Nagasaki Pref. (JP)
Inventor : Hisatome, Nagao, c/o Nagasaki
Shipyards & Eng. Works
Mitsubishi Jukogyo K.K., 1-1, Akunoura-machi
Nagasaki, Nagasaki Pref. (JP)


Inventor : Araki, Tadayoshi, c/o Nagasaki
Shipyards & Eng. Works
Mitsubishi Jukogyo K.K., 1-1, Akunoura-machi
Nagasaki, Nagasaki Pref. (JP)
Inventor : Ikeda, Koji, c/o Nagasaki Shipyards &
Eng. Works
Mitsubishi Jukogyo K.K., 1-1, Akunoura-machi
Nagasaki, Nagasaki Pref. (JP)
Inventor : Nagata, Katsumi, c/o Nagasaki
Shipyards & Eng. Works
Mitsubishi Jukogyo K.K., 1-1, Akunoura-machi
Nagasaki, Nagasaki Pref. (JP)
Inventor : Sasai, Tetsuichi c/o Nagasaki
Shipyards & Eng. Works
Mitsubishi Jukogyo K.K., 1-1, Akunoura-machi
Nagasaki, Nagasaki Pref. (JP)
Inventor : Notomi, Akira, c/o Nagasaki
Technical Institute
Mitsubishi Jukogyo K.K., 717-1,
Fukahori-machi
5-chome, Nagasaki, Nagasaki Pref. (JP)
Inventor : Yamauchi, Yasuhiro, c/o Nagasaki
Technical Inst.
Mitsubishi Jukogyo K.K., 717-1,
Fukahori-machi
5-chome, Nagasaki, Nagasaki Pref. (JP)

(74) Representative : Lawson, David Glynn et al
MARKS & CLERK 57-60 Lincoln's Inn Fields
London WC2A 3LS (GB)

(54) Solid electrolyte fuel cell.

(57) A solid oxide fuel cell comprises an insulating layer (1a) formed on a base tube (1) or a base tube (1) itself having electrically insulating properties, and a generating layer formed by successively laminating a fuel electrode (2), a solid electrolyte (3) and an air electrode (5) on the insulating layer (1a), in which fuel cell a chemically stable reaction-preventive film is preferably formed between the insulating layer (1c) or the insulating base tube (1) and the fuel layer, and which fuel cell is preferably heat treated. Also, a solid oxide fuel cell may comprise a ceramic base (21), a fuel electrode material (22) and an electrolyte material (23) thermal-sprayed and sintered on the ceramic base member (21), and an air electrode material (24) thermal-sprayed on the fuel electrode material (22) and the electrolyte material (23).

FIG. 1



EP 0 516 417 A1